

DATASHEET: P004 PAGE 1 OF 1 ISSUE NO. 02

## ANNULAR EDGE REPLACEMENT SIGHT GLASS

After a number of years processing this product for Corning, we are now in a position to offer direct replacements for these glasses

The original Annular Edge glasses were molded and the raised rims were ground flat to give 1/2" wide gasket surfaces. Our glasses are ground and polished to provide a full ¾" thickness\* across the diameter giving improved visibility, pressure rating and the ability to fit wider gaskets

\* The original glasses had a pressure rating based on minimum recess thickness of 5/8"

## **TYPICAL PROPERTIES**

## Plain (Annealed) 209° C (409° F) Max Service

Part No	Dia."	PSI	Bolts
695620	4	150	6
	_		
695610	5	100	6
692540	6	60	6
694790	6 3/4	45	6
694800	8 3/8	30	8

## High Pressure (Toughened) 260 °C (500°F) Max Service

Part No	Dia."	PSI	Bolts
695621	4	450	6
695611	5	300	6
692541	6	180	6
694791	6 3/4	135	6
694801	8 3/8	90	8

For reference, the original Corning part numbers are shown

SPECTRAGLASS Limited Unit 2, Inveralmond Close, Inveralmond Industrial Estate, Perth PH1 3TT

Tel: 01738 638358 Fax: 01738 634744

info@spectraglass.com www.spectraglass.com